



Real Time Processing Documentation

Version 10
August, 2010

Credimetrics.com

Technical Operations Centre
1935 Camino Vida Roble, Suite 260
Carlsbad, CA 92008
760.431.4300
760.431.4304 Fax

This documentation is the property of Luxor Technologies, Inc. and PRBC and is considered to be strictly confidential. It contains information intended only for the person to whom it is transmitted or delivered. With the receipt of this document, recipient acknowledges and agrees that the recipient will not copy, fax, reproduce, divulge, or distribute this documentation, in whole or in part, without the express written consent of PRBC.

Credimetrics Online Order Processing

REAL TIME PROCESSING DOCUMENTATION.....	1
OVERVIEW	3
PRODUCTS.....	3
PASSING PRODUCT REQUESTS TO	4
<i>Notes on the MRG_XML Product.....</i>	4
<i>Notes on the MRG_XMLSTACK Product.....</i>	4
<i>Notes on the MRG_RPTCOM Product.....</i>	5
<i>Notes on the MRG_RPTDTC Product.....</i>	5
<i>Notes on the MRG_DECISION Product.....</i>	5
<i>Notes on the OFACTTY/OFACXML Products</i>	5
<i>Notes on the EFXPASSTHRU, EXPPASSTHRU and TUCPASSTHRU Products.....</i>	6
REALTIME PROCESSING.....	6
HOW REALTIME PROCESSING WORKS	7
PLACING THE REAL TIME ORDER.....	7
<i>Merge SOAP Listener</i>	7
<i>RequestXML.....</i>	8
<i>Request XML.....</i>	11
Notes on XMLRequest	12
<i>Merge ResponseXML.....</i>	13
<i>ResponseXML</i>	14
Notes on XMLResponse	15
<i>MRG_XML/MRG_XMLSTACK Credit Data.....</i>	16
<i>Merged Bureau Distinction.....</i>	17
<i>MRG_XMLSTACK Stacked Merge Data.....</i>	17
USING THE CLIENT OBJECT	19
CMMERGE CLIENT METHODS	19
<i>CreateXMLRequestString</i>	19
<i>GetResponse.....</i>	19
<i>PlaceOrder.....</i>	19
<i>SetRequestor</i>	19
<i>WriteResponseToDisk.....</i>	19
CMMERGE CLIENT PROPERTIES	19
<i>CompletionDate</i>	19
<i>OrderKey.....</i>	20
<i>OrderStatus.....</i>	20
<i>OrderMessage.....</i>	20
CMMERGE CLIENT CLASSES	20

<i>CONSUMER</i>	20
Properties:	20
ECOA	20
Methods:	20
SetSubject	20
SetSubjectCRA	20
SetSpouse	20
SetSpouseCRA	20
SetCurrentAddress	20
SetFormerAddress	20
<i>DATASOURCES</i>	20
Properties:	21
UseEquifax	21
UseExperian	21
UseTransUnion	21
UsePRBC	21
PRBCGetUpdated	21
Methods:	21
SetEquifax	21
SetExperian	21
SetTransUnion	21
SetPRBC	22
<i>DECISIONS</i>	22
Properties:	22
ProfileName	22
ResultsNameList	22
XML	22
Methods:	22
AddParameters	22
GetResultsByName	22
<i>PRODUCTS</i>	22
Properties:	22
ProductsList	22
Methods:	22
AddProduct	22
RemoveProduct	22
RemoveAllProducts	22
<i>REQUEST</i>	22
CLIENT OBJECT SAMPLES	23
ORDERING MERGED PRODUCTS	23
ORDERING PASS THROUGH PRODUCTS	24
ORDERING PRBC XML AND FICO EXPANSION SCORE	25

OVERVIEW

The system provides an online, real-time response to requests for merged and unmerged credit data products. Using the 128 bit encryption protection of SSL, the system securely protects your request information and returned credit information over the world wide web.

The system performs the following functions:

- o Accepts your online request.
- o Validates your login account.
- o Validates your consumer identification information.
- o Validates your product options.
- o Retrieves previously acquired credit bureau files.
- o Accesses the national credit repositories using your subscription information and retrieves credit bureau files.
- o Optionally merges the bureau data.
- o Returns back merged XML or merged Report products.
- o Returns back decision results from your lending profile.

PRODUCTS

The Credimetrics system provides a host of credit reporting products aimed at a variety of needs. Products range from simple credit files passed to the requestor directly from the national credit repositories, to merged credit files and online decisions based upon your credit policies.

The following is a list of the products currently provided:

Product Code	Product Description
MRG_XML	Merged Credit file in an xml format.
MRG_XMLSTACK	Merged Credit file in an xml format where merged segments are followed by intra-bureau merged segments from each of the three national credit repositories
PRBC_XML	PRBC Bill Payment Score Card and Account history in XML Format.
PRBC_FICO_XML	FICO Expansion Score in XML format derived from PRBC data and passed input Cra segment.
MRG_RPTDTC	Merged Direct-to-consumer credit report in PDF Format.
MRG_RPTCOM	Merged Common, lending report.
MRG_DECISION	Automated lending decision.
OFACRPT	Suspicious persons report based upon entered name and address.
OFACXML	Suspicious persons XML file based upon entered name and address.
EFXPASSTHRU	Credit file passed directly from Equifax to requestor.
EFXCREDITCPU	Equifax cpu Credit file passed to requestor.
EFXCREDITTTY	Equifax tty Credit report passed to requestor.
EFXDTECTTY	Equifax tty DTEC report passed to requestor.

EXPPASSTHRU	Credit file passed directly from Experian to requestor.
EXPCREDITCPU	Experian cpu Credit file passed to requestor.
EXPCREDITTTY	Experian tty Credit report passed to requestor.
EXPSOCIALTTY	Experian tty Social report passed to requestor.
EXPCOLLTTY	Experian tty Collection report passed to requestor.
EXPEMPLTTY	Experian tty Employment report passed to requestor.
EXPBULSEYETTY	Experian tty BullsEye report passed to requestor.
TUCPASSTHRU	Credit file passed directly from TransUnion to requestor.
TUCCREDITCPU	TransUnion cpu credit file passed to requestor.
TUCCREDITTTY	TransUnion tty credit report passed to requestor.
TUCTRACETTY	TransUnion tty Trace report passed to requestor.
TUCTRPLUSTTY	TransUnion tty TracePlus report passed to requestor.
TUCFACTTTY	TransUnion tty Fact report passed to requestor.

Passing Product Requests to

provides an XML request layout that enables multiple product requests to be made. The product code is passed in the CODE attribute of the PRODUCT element within the CMPRODUCTS section of the CMREQUEST XML document.

There is also support for an optional OPTIONS attribute where custom processing options can be submitted. These options are comma delimited name value pairs and are provided by administration personnel.

Notes on the MRG_XML Product

The MRG_XML product returns an XML document containing credit history data on the consumer identified in the order. The XML document is contained in its entirety inside the CDATA section of the MRG_XML product response.

The data represents a merged view of any number of bureau or bill payment data sources requested. For example, if only an Equifax bureau is selected, the returned XML document represents a merge of Equifax data within itself, thus removing any duplicates that may be found within the credit file.

Notes on the MRG_XMLSTACK Product

The MRG_XMLSTACK product returns an XML document containing credit history data on the consumer identified in the order. The XML document is contained in its entirety inside the CDATA section of the MRG_XMLSTACK product response.

The data represents a stacked merged view of any number of bureau data sources requested. The merged element is followed by up to three child elements, one for each of the national credit repositories. The elements of the child are the same as the elements of the merged parent with the addition of an INTRA child element containing a Bureau attribute. The possible values of the Bureau attribute are "EFX" for Equifax, "EXP" for

Experian and "TUC" for TransUnion. The child element reflects information derived solely from the bureau identified by the Bureau attribute.

Notes on the MRG_RPTCOM Product

The MRG_RPTCOM product returns a TTY report that is 100 characters wide and 60 lines per page; and containing credit history data on the consumer identified in the order. The TTY report is contained in its entirety inside the CDATA section of the MRG_RPTCOM product response.

The data represents a merged view of any number of bureau data or bill payment sources requested. For example, if only an Equifax bureau is selected, the returned TTY document represents a merge of Equifax data within itself, thus removing any duplicates that may be found within the credit file.

Notes on the MRG_RPTDTC Product

The MRG_RPTDTC product returns a direct-to-consumer cred report that is formatted in the Adobe Acrobat PDF format; and containing credit history data on the consumer identified in the order. The PDF report is contained in its entirety inside the CDATA section of the MRG_RPTDTC product response.

The data represents a merged view of any number of bureau data sources requested. For example, if only an Equifax bureau is selected, the returned PDF document represents a merge of Equifax data within itself, thus removing any duplicates that may be found within the credit file.

Notes on the MRG_DECISION Product

The MRG_DECISION product returns a set of decision results from a customized decision profile stored in the system. This product may need additional information in order to process the script such as 'Loan Amount' or 'Stated Income' or other such variables not normally found in a credit data set.

To convey these application-oriented variables; and to specify the decision profile name to execute, a section exists in the CMREQUEST XML document. In the CMREQUEST section, the decision profile name is set in the PROFILENAME element; and the optional parameters are set in multiple PARAMETER elements using the NAME and VALUE attributes. The NAME represents the name that the script will use to refer to the VALUE.

Notes on the OFACTTY/OFACXML Products

The OFACTTY and OFACXML products perform a search of the Suspicious Persons data provided by the United States Treasury Department. This product requires no DATASOURCE to be selected as the data is completely located within the system. The data is updated daily from a feed from the Treasury Department.

The search is based upon the entered Subject Name and/or Current Address. Both products can be returned on a single request just as other products are ordered in the same transaction. Each product is encased in its own CDATA section.

The OFACTTY is a 100 character wide TTY report with no page breaks. It lists the date, time and subject on which the search is conducted; and lists each possible match along with aliases and addresses that match the suspicious person listed.

The OFACXML product is a direct equivalent of the TTY product and is the basis upon which the TTY product is built.

Notes on the EFXPASSTHRU, EXPPASSTHRU and TUCPASSTHRU Products

The 'passthru' products provided by are intended to serve those requests where the original bureau data is required. Using these product codes may be considered illogical when ordering merged products unless the 'passthru' product is a credit file in cpu format. This is because the merged products depend on cpu format credit files to operate.

When one of the 'passthru' product codes is submitted, the desired product from each of the bureaus to be passed is set in the PASSTHRUPRODUCT field for the particular bureau in the CMDATASOURCES section of the CMREQUEST XML document.

While it is possible to receive multiple products, only a single credit file from each of the repositories can be obtained through via a single request. Hence, a EFXPASSTHRU of a EFXDTECTTY report cannot be made in the same transaction that requests a three bureau merged credit report.

REALTIME PROCESSING

The system is engineered to accept a single, individual request for merged or unmerged credit data via a published Web Service. This service expects a request XML stream identifying the customer, the customer's repository subscription information, the consumer's identification information and general request information identifying a customer reference number, individual or joint indications, which bureaus to process and what products to return. Multiple products can be returned on a single request.

When the system receives the request XML via the Web Service, it begins processing the request; and returns a responseXML when the product is completed. Hence, the process is REALTIME.

During this processing, telecommunication tasks are conducted with the national credit and bill payment repositories. When the telecommunications processes are concluded, the products are fulfilled and returned.

It is possible for one or more of the national repositories to return a No Record; or have some outage. The outage can be temporary or an outage that is caused by some problem with the requesting information such as the customer's bureau subscriber code data.

In any case, the system continues and produces the requested products based on what credit data it has. An indication is made in the response that identifies the product as complete or incomplete and states the reason why it would be incomplete.

In the response is also a unique order number. Using this order number in a subsequent order will re-use any existing, good credit data; and will re-order any missing credit data.

How Realtime Processing Works

The realtime ordering process consists of:

1. Receiving the customer's order in a Request XML file via a Web Service.
2. Validating it.
3. Returning a response XML immediately if validation fails.
4. Retrieving any existing, good credit data based upon the inclusion of a valid, existing OrderKey.
5. Ordering any new or missing data based upon the bureau's being requested.
6. Fulfilling the requested products.
7. Returning the products back in a response XML file.

Placing the Real Time Order

Currently the only means of placing a Real Time Order is via the SOAP Listener. This SOAP Listener is a Web Service that accepts an XMLRequest and returns an XMLResponse.

Merge SOAP Listener

The Credimetrics Merge SOAP Listener is a published Web Service. The interface definition is found at:

<https://webservice.credimetrics.com/CMMergeListener.wsdl>

This Web Service Definition Language file is shown below:

```
<?xml version="1.0" encoding="UTF-8" ?>
- <!--
Generated 12/02/02 by Microsoft SOAP Toolkit WSDL File Generator, Version 1.02.813.0

- <definitions name="CMMergeListener" targetNamespace="http://tempuri.org/wsdl/"
xmlns:wsdl="http://tempuri.org/wsdl/" xmlns:typens="http://tempuri.org/type"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:stk="http://schemas.microsoft.com/soap-toolkit/wsdl-extension"
xmlns="http://schemas.xmlsoap.org/wsdl/" >
```

```

- <types>
  <schema targetNamespace="http://tempuri.org/type"
    xmlns="http://www.w3.org/2001/XMLSchema" xmlns:SOAP-
    ENC="http://schemas.xmlsoap.org/soap/encoding/"
    xmlns:wSDL="http://schemas.xmlsoap.org/wsdl/" elementFormDefault="qualified" />
  </types>
- <message name="Order.Place">
  <part name="RequestXML" type="xsd:string" />
  <part name="ResponseXML" type="xsd:base64Binary" />
  </message>
- <message name="Order.PlaceResponse">
  <part name="ResponseXML" type="xsd:base64Binary" />
  </message>
- <portType name="OrderSoapPort">
- <operation name="Place" parameterOrder="RequestXML ResponseXML">
  <input message="wsdlIns:Order.Place" />
  <output message="wsdlIns:Order.PlaceResponse" />
  </operation>
</portType>
- <binding name="OrderSoapBinding" type="wsdlIns:OrderSoapPort">
  <stk:binding preferredEncoding="UTF-8" />
  <soap:binding style="rpc" transport="http://schemas.xmlsoap.org/soap/http" />
- <operation name="Place">
  <soap:operation soapAction="http://tempuri.org/action/Order.Place" />
- <input>
  <soap:body use="encoded" namespace="http://tempuri.org/message/"
    encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" />
  </input>
- <output>
  <soap:body use="encoded" namespace="http://tempuri.org/message/"
    encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" />
  </output>
  </operation>
</binding>
- <service name="CMMergeListener">
- <port name="OrderSoapPort" binding="wsdlIns:OrderSoapBinding">
  <soap:address location="https://webservice..com/CMMergeListener.WSDL" />
  </port>
</service>
</definitions>

```

RequestXML

The request sent to Merge contains the following information:

- Order information – Customer reference number, Previous OrderKey, Which Bureaus to Use, Individual or Joint accessing, What Products to return.
- Customer Information – Customer login id and password.
- Data Source Information – Subscriber codes for each of the national credit and bill payment repositories, or a profile name of a pre-defined subscription profile, or a stream of raw bureau data in lieu of accessing

the national repositories. Additionally, the name of a pass-thru product to be returned directly from the repository.

- o Consumer's identification information – Subject Name, Spouse Name, Current and Former Address information.
- o Product request information – A set of product codes reflecting the products requested.
- o Decision parameters – The decision profile name and a set of parameter names and values.

The RequestXML schema can be found at:

<https://www..com/merge/Schemas/CMRequest.xsd>

The RequestXML schema is shown below:

```
<?xml version="1.0" encoding="UTF-8" ?>
- <!--
  edited with XMLSPY v5 rel. 4 U (http://www.xmlspy.com) by Robb Murdock (Luxor Technologies, Inc.)
  W3C Schema generated by XMLSPY v5 rel. 4 U (http://www.xmlspy.com)
-->
- <xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" elementFormDefault="qualified">
- <xs:element name="ADDON">
- <xs:complexType>
  <xs:attribute name="MODELID" type="xs:string" />
</xs:complexType>
</xs:element>
- <xs:element name="ADDRESS">
- <xs:complexType>
  <xs:attribute name="TYPE" type="xs:string" use="required" />
  <xs:attribute name="ADDRESS" type="xs:string" use="required" />
  <xs:attribute name="CITY" type="xs:string" use="required" />
  <xs:attribute name="STATE" type="xs:string" use="required" />
  <xs:attribute name="POSTALCODE" type="xs:string" use="required" />
</xs:complexType>
</xs:element>
- <xs:element name="CMCONSUMERS">
- <xs:complexType>
- <xs:sequence>
  <xs:element ref="SUBJECT" />
  <xs:element ref="SPOUSE" />
  <xs:element ref="ADDRESS" />
</xs:sequence>
  <xs:attribute name="ECO" type="xs:string" use="required" />
</xs:complexType>
</xs:element>
- <xs:element name="CMDATASOURCES">
- <xs:complexType>
- <xs:sequence>
  <xs:element ref="EQUIFAX" />
  <xs:element ref="EXPERIAN" />
  <xs:element ref="TRANSUNION" />
  <xs:element ref="PRBC" />
</xs:sequence>
```

```

    </xs:complexType>
  </xs:element>
- <xs:element name="CMDECISION">
- <xs:complexType>
- <xs:sequence>
  <xs:element ref="PARAMETER" />
</xs:sequence>
  <xs:attribute name="PROFILENAME" type="xs:string" use="required" />
</xs:complexType>
</xs:element>
- <xs:element name="CMPRODUCTS">
- <xs:complexType>
- <xs:sequence>
  <xs:element ref="PRODUCT" />
</xs:sequence>
</xs:complexType>
</xs:element>
- <xs:element name="CMREQUEST">
- <xs:complexType>
- <xs:sequence>
  <xs:element ref="CMREQUESTOR" />
  <xs:element ref="CMDATASOURCES" />
  <xs:element ref="CMCONSUMERS" />
  <xs:element ref="CMPRODUCTS" />
  <xs:element ref="CMDECISION" />
</xs:sequence>
  <xs:attribute name="REFERENCENUMBER" type="xs:string" use="required" />
  <xs:attribute name="ORDERKEY" type="xs:string" use="required" />
</xs:complexType>
</xs:element>
- <xs:element name="CMREQUESTOR">
- <xs:complexType>
  <xs:attribute name="LOGINNAME" type="xs:string" use="required" />
  <xs:attribute name="PASSWORD" type="xs:string" use="required" />
</xs:complexType>
</xs:element>
- <xs:element name="CRA">
  <xs:complexType />
</xs:element>
- <xs:element name="EQUIFAX">
- <xs:complexType>
- <xs:sequence>
  <xs:element ref="SCORE" />
  <xs:element ref="ADDON" />
</xs:sequence>
  <xs:attribute name="PREAMBLE" type="xs:string" use="required" />
  <xs:attribute name="SUBCODE" type="xs:string" use="required" />
  <xs:attribute name="PASSWORD" type="xs:string" use="required" />
  <xs:attribute name="PROFILE" type="xs:string" use="required" />
  <xs:attribute name="PURPOSE" type="xs:string" use="required" />
  <xs:attribute name="PURPOSEUSER" type="xs:string" use="required" />
</xs:complexType>
</xs:element>
- <xs:element name="EXPERIAN">
- <xs:complexType>
- <xs:sequence>
  <xs:element ref="SCORE" />
  <xs:element ref="ADDON" />
</xs:sequence>
  <xs:attribute name="PREAMBLE" type="xs:string" use="required" />
  <xs:attribute name="SUBCODE" type="xs:string" use="required" />
  <xs:attribute name="PASSWORD" type="xs:string" use="required" />
  <xs:attribute name="PROFILE" type="xs:string" use="required" />
  <xs:attribute name="PURPOSE" type="xs:string" use="required" />
  <xs:attribute name="PURPOSEUSER" type="xs:string" use="required" />
</xs:complexType>
</xs:element>
- <xs:element name="GETUPDATED">
  <xs:complexType />
</xs:element>

```

```

- <xs:element name="PARAMETER">
- <xs:complexType>
  <xs:attribute name="NAME" type="xs:string" use="required" />
  <xs:attribute name="VALUE" type="xs:string" use="required" />
  </xs:complexType>
</xs:element>

- <xs:element name="PRODUCT">
- <xs:complexType>
  <xs:attribute name="CODE" type="xs:string" use="required" />
  <xs:attribute name="OPTIONS" type="xs:string" use="required" />
  </xs:complexType>
</xs:element>

- <xs:element name="SCORE">
- <xs:complexType>
  <xs:attribute name="MODELID" type="xs:string" />
  </xs:complexType>
</xs:element>

- <xs:element name="SPOUSE">
- <xs:complexType>
- <xs:sequence>
  <xs:element ref="CRA" />
  </xs:sequence>
  <xs:attribute name="SURNAME" type="xs:string" use="required" />
  <xs:attribute name="FIRSTNAME" type="xs:string" use="required" />
  <xs:attribute name="MIDNAME" type="xs:string" use="required" />
  <xs:attribute name="GENERATION" type="xs:string" use="required" />
  <xs:attribute name="SSN" type="xs:string" use="required" />
  <xs:attribute name="AGE" type="xs:string" use="required" />
  </xs:complexType>
</xs:element>

- <xs:element name="SUBJECT">
- <xs:complexType>
- <xs:sequence>
  <xs:element ref="CRA" />
  </xs:sequence>
  <xs:attribute name="SURNAME" type="xs:string" use="required" />
  <xs:attribute name="FIRSTNAME" type="xs:string" use="required" />
  <xs:attribute name="MIDNAME" type="xs:string" use="required" />
  <xs:attribute name="GENERATION" type="xs:string" use="required" />
  <xs:attribute name="SSN" type="xs:string" use="required" />
  <xs:attribute name="AGE" type="xs:string" use="required" />
  </xs:complexType>
</xs:element>

- <xs:element name="TRANSUNION">
- <xs:complexType>
- <xs:sequence>
  <xs:element ref="SCORE" />
  <xs:element ref="ADDON" />
  </xs:sequence>
  <xs:attribute name="MARKET" type="xs:string" use="required" />
  <xs:attribute name="SUBMARKET" type="xs:string" use="required" />
  <xs:attribute name="SUBCODE" type="xs:string" use="required" />
  <xs:attribute name="PASSWORD" type="xs:string" use="required" />
  <xs:attribute name="INDUSTRYCODE" type="xs:string" use="required" />
  <xs:attribute name="PROFILE" type="xs:string" use="required" />
  <xs:attribute name="PURPOSE" type="xs:string" use="required" />
  <xs:attribute name="PURPOSEUSER" type="xs:string" use="required" />
  </xs:complexType>
</xs:element>
</xs:schema>

```

Request XML

A sample RequestXML xml file can be found at:

<https://www..com/Merge/Schemas/CMRequest.xml>

The RequestXML sample XML file is shown below:

```

<?xml version="1.0" encoding="UTF-8" ?>
- <!--
  edited with XMLSPY v5 rel. 4 U (http://www.xmlspy.com) by Robb Murdock (Luxor Technologies, Inc.)
  Copyright 2004 Luxor Technologies, Inc.
-->
- <CMREQUEST REFERENCENUMBER="" ORDERKEY="">
  <CMREQUESTOR LOGINNAME="" PASSWORD="" />
- <CMDATASOURCES>
- <EQUIFAX PREAMBLE="" SUBCODE="" PASSWORD="" PROFILE="" PURPOSE="" PURPOSEUSER="">
  <SCORE />
  <ADDON MODELID="" />
  </EQUIFAX>
- <EXPERIAN PREAMBLE="" SUBCODE="" PASSWORD="" PROFILE="" PURPOSE="" PURPOSEUSER="">
  <SCORE MODELID="" />
  <ADDON />
  </EXPERIAN>
- <TRANSUNION MARKET="" SUBMARKET="" SUBCODE="" PASSWORD="" INDUSTRYCODE="" PROFILE=""
  PURPOSE="" PURPOSEUSER="">
  <SCORE MODELID="" />
  <ADDON />
  </TRANSUNION>
  </CMDATASOURCES>
- <CMCONSUMERS ECOA="">
- <SUBJECT SURNAME="" FIRSTNAME="" MIDNAME="" GENERATION="" SSN="" AGE="">
  <CRA />
  </SUBJECT>
- <SPOUSE SURNAME="" FIRSTNAME="" MIDNAME="" GENERATION="" SSN="" AGE="">
  <CRA />
  </SPOUSE>
  <ADDRESS TYPE="" ADDRESS="" CITY="" STATE="" POSTALCODE="" />
  </CMCONSUMERS>
- <CMPRODUCTS>
  <PRODUCT CODE="" OPTIONS="" />
  </CMPRODUCTS>
- <CMDECISION PROFILENAME="">
  <PARAMETER NAME="" VALUE="" />
  </CMDECISION>
</CMREQUEST>

```

Notes on XMLRequest

The following is a partial data dictionary for the RequestXML file

Node	Attribute	Notes
CMREQUEST	REFERENCENUMBER	Optional. Value is extracted and used in CMResponse to sync the response to the request.
CMREQUEST	ORDERKEY	Optional. Used to reference an existing order's bureau data. Useful for re-ordering from a previously incomplete order.
CMREQUEST	ECOA	Optional. If used must contain I for Individual or J for Joint. I is default.
CMCONSUMER/SUBJECT	SURNAME,FIRSTNAME & SSN	Required. SSN must be 9 digit numeric.
CMCONSUMER/SPOUSE	SURNAME,FIRSTNAME & SSN	Optional but required if ECOA is J.
CMCONSUMER/SUBJECT OR SPOUSE	GENERATION	Optional. Valid values are: J,S,JR,SR,1-6,I-VI
CMPRODUCTS/PRODUCT	CODE	Required. MRG_XML – Merged credit data suitable for normal merged applications.

		<p>MRG_XMLSTACK – Merged credit data suitable for normal or stacked merged applications.</p> <p>MRG_RPTCOM – Formatted consumer lending credit report.</p> <p>MRG_RPTDTC – Formatted direct to consumer report in PDF format.</p> <p>MRG_DECISION – Decision results based upon passed parms and customer decision script profile.</p> <p>OFACTTY – Suspicious persons report in TTY format.</p> <p>OFACTXML – Suspicious persons report in XML format.</p> <p>NOTE: For other products, see Product Codes in the Products section of this document.</p>
	OPTIONS	Optional. Contains comma delimited string of name, value option pairs. See Credimetrics administration personnel for values.
CMDECISION	PROFILENAME	Required if MRG_DECISION product code is specified. Name of a customized decision profile script to be used to provide decision.
CMDECISION/PARAMETER	NAME/VALUE	Optional. Set of name value pairs representing specific parameters to be passed to the script for processing.
CMDATASOURCES/bureau	Various elements	Subscriber code information for each of the requested bureaus including Permissible Purpose code and the End User name associated with the purpose code. Alternatively, all subscriber code info can be stored at Credmetrics and referenced by the PROFILE name.

Merge ResponseXML

The response returned from Credimetrics Merge contains the following information:

- Order information – Customer reference number, Assigned OrderKey, CompletionStatus, CompletionDate and CompletionMessage.
- Error Information – If any errors or found a set of errors are returned containing an ErrorCode and ErrorMessage.
- Data – Returned products containing Type of data and the returned product in a CDATA section.

ResponseXML

The ResponseXML schema can be found at:

<https://webservice.credimetrics.com/Schemas/CMResponse.xsd>

The ResponseXML schema is shown below:

```
<?xml version="1.0" encoding="UTF-8" ?>
<!--
edited with XMLSPY v5 rel. 2 U (http://www.xmlspy.com) by Robb Murdock (Luxor Technologies,
Inc.)
-->
<!--
W3C Schema generated by XMLSPY v5 rel. 2 U (http://www.xmlspy.com)
-->
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema"
  elementFormDefault="qualified">
  <xs:element name="CMDData">
    <xs:complexType mixed="true">
      <xs:attribute name="ProductCode" type="xs:string" use="required" />
      <xs:attribute name="StatusCode" type="xs:string" use="required" />
      <xs:attribute name="StatusMessage" type="xs:string" use="required" />
    </xs:complexType>
  </xs:element>
  <xs:element name="CMDDataSets">
    <xs:complexType>
      <xs:sequence>
        <xs:element ref="CMDData" />
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="CMErrors">
    <xs:complexType>
      <xs:sequence>
        <xs:element ref="Error" />
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="CMResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element ref="CMErrors" />
        <xs:element ref="CMDDataSets" />
      </xs:sequence>
      <xs:attribute name="ReferenceNumber" type="xs:string" use="required" />
      <xs:attribute name="OrderKey" type="xs:string" use="required" />
      <xs:attribute name="OrderCompletedDate" type="xs:string" use="required" />
      <xs:attribute name="OrderStatus" type="xs:string" use="required" />
      <xs:attribute name="OrderMessage" type="xs:string" use="required" />
    </xs:complexType>
  </xs:element>
  <xs:element name="Error">
    <xs:complexType>
      <xs:attribute name="Code" type="xs:string" use="required" />
      <xs:attribute name="Message" type="xs:string" use="required" />
    </xs:complexType>
  </xs:element>
</xs:schema>
```

A sample ResponseXML xml file can be found at:

<https://webservice.credimetrics.com/Schemas/CMResponse.xml>

The ResponseXML sample XML file is shown below:

```
<CMRESPONSE REFERENCENUMBER="" ORDERKEY="" ORDERCOMPLETEDDATE="" ORDERSTATUS=""
ORDERMESSAGE="" XMLNS:XSI="HTTP://WWW.W3.ORG/2001/XMLSCHEMA-INSTANCE">
  <CMERRORS>
    <ERROR CODE="" MESSAGE=""/>
  </CMERRORS>
  <CMDATASETS>
    <CMDATA PRODUCTCODE="" STATUSCODE="" STATUSMESSAGE=""/>
  </CMDATASETS>
</CMRESPONSE>
```

Notes on XMLResponse

The following is a partial data dictionary for the ResponseXML file

Node	Attribute	Notes														
CMRESPONSE	REFERENCENUMBER	Optional. Will be returned and contain same value as found in CMRequest/ReferenceNumber														
CMRESPONSE	ORDERKEY	Optional. Will contain either new or existing assigned OrderKey if a product is returned. Will not be returned if input transaction could not be processed.														
CMRESPONSE	ORDERCOMPLETEDATE	Optional. Will be set if the order is deemed complete. That is, the OrderStatus is set to Complete.														
CMRESPONSE	ORDERSTATUS, ORDERMESSAGE	<p>Constant. Status Codes and English text to indicate status of the order.</p> <table border="1"> <thead> <tr> <th>CODE</th> <th>DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>Order Completed</td> </tr> <tr> <td>1</td> <td>Order Incomplete</td> </tr> <tr> <td>2</td> <td>Order Not processed</td> </tr> </tbody> </table> <p>The OrderMessage may contain extended verbiage to expound upon status.</p>	CODE	DESCRIPTION	0	Order Completed	1	Order Incomplete	2	Order Not processed						
CODE	DESCRIPTION															
0	Order Completed															
1	Order Incomplete															
2	Order Not processed															
CMRESPONSE/ERRORS		Optional. Will contain Error Nodes if any input or processing errors were encountered.														
ERROR	CODE, MESSAGE	<p>Constant if Error Node is present. Codes and Messages indicating any form of error.</p> <table border="1"> <thead> <tr> <th>CODE</th> <th>DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td>0001</td> <td>Communications failure. <i>(Returned from the (CMMergeClient.Request object only).</i></td> </tr> <tr> <td>1001</td> <td>Customer invalid</td> </tr> <tr> <td>1002</td> <td>Order invalid</td> </tr> <tr> <td>1003</td> <td>Decision processing error</td> </tr> <tr> <td>1004</td> <td>Invalid XML request data</td> </tr> <tr> <td>1005</td> <td>Login processing error</td> </tr> </tbody> </table>	CODE	DESCRIPTION	0001	Communications failure. <i>(Returned from the (CMMergeClient.Request object only).</i>	1001	Customer invalid	1002	Order invalid	1003	Decision processing error	1004	Invalid XML request data	1005	Login processing error
CODE	DESCRIPTION															
0001	Communications failure. <i>(Returned from the (CMMergeClient.Request object only).</i>															
1001	Customer invalid															
1002	Order invalid															
1003	Decision processing error															
1004	Invalid XML request data															
1005	Login processing error															

		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="width: 15%;">1006</td><td>Product processing error</td></tr> <tr><td>1007</td><td>Data sources processing error</td></tr> <tr><td>1008</td><td>Bureau server processing error</td></tr> <tr><td>1009</td><td>Product code parsing error</td></tr> <tr><td>1010</td><td>Order completion processing error.</td></tr> <tr><td>2001</td><td>Bureau communications Error</td></tr> <tr><td>2002</td><td>Bureau data incomplete</td></tr> <tr><td>2101</td><td>Equifax timed out</td></tr> <tr><td>2102</td><td>Equifax communications Error</td></tr> <tr><td>2103</td><td>Equifax returned error.</td></tr> <tr><td>2201</td><td>Experian timed out</td></tr> <tr><td>2202</td><td>Experian communications Error</td></tr> <tr><td>2203</td><td>Experian returned error.</td></tr> <tr><td>2301</td><td>TransUnion timed out</td></tr> <tr><td>2302</td><td>TransUnion communications Error</td></tr> <tr><td>2303</td><td>TransUnion returned error.</td></tr> <tr><td>3000</td><td>Merge processing Error</td></tr> <tr><td>4000</td><td>Decision error.</td></tr> </table> <p>Message may contain extended verbiage to expand upon error.</p>	1006	Product processing error	1007	Data sources processing error	1008	Bureau server processing error	1009	Product code parsing error	1010	Order completion processing error.	2001	Bureau communications Error	2002	Bureau data incomplete	2101	Equifax timed out	2102	Equifax communications Error	2103	Equifax returned error.	2201	Experian timed out	2202	Experian communications Error	2203	Experian returned error.	2301	TransUnion timed out	2302	TransUnion communications Error	2303	TransUnion returned error.	3000	Merge processing Error	4000	Decision error.
1006	Product processing error																																					
1007	Data sources processing error																																					
1008	Bureau server processing error																																					
1009	Product code parsing error																																					
1010	Order completion processing error.																																					
2001	Bureau communications Error																																					
2002	Bureau data incomplete																																					
2101	Equifax timed out																																					
2102	Equifax communications Error																																					
2103	Equifax returned error.																																					
2201	Experian timed out																																					
2202	Experian communications Error																																					
2203	Experian returned error.																																					
2301	TransUnion timed out																																					
2302	TransUnion communications Error																																					
2303	TransUnion returned error.																																					
3000	Merge processing Error																																					
4000	Decision error.																																					
CMRESPONSE/DATASETS/DATA	PRODUCTCODE	<p>Defines type of data to follow.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 30%;">TYPE</th> <th>DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td>MRG_XML</td> <td>Merged credit data in XML format</td> </tr> <tr> <td>MRG_RPTCOM</td> <td>Merged credit report in TTY format</td> </tr> <tr> <td>MRG_RPTDTC</td> <td>Merged credit Report in PDF format.</td> </tr> <tr> <td>MRG_DECISION</td> <td>Decision results in XML format</td> </tr> <tr> <td>OFACRPT</td> <td>Suspicious persons report in TTY format</td> </tr> <tr> <td>OFACXML</td> <td>Suspicious persons report in XML format</td> </tr> </tbody> </table> <p>For other products see the Product Codes in the Product Section of this document.</p>	TYPE	DESCRIPTION	MRG_XML	Merged credit data in XML format	MRG_RPTCOM	Merged credit report in TTY format	MRG_RPTDTC	Merged credit Report in PDF format.	MRG_DECISION	Decision results in XML format	OFACRPT	Suspicious persons report in TTY format	OFACXML	Suspicious persons report in XML format																						
TYPE	DESCRIPTION																																					
MRG_XML	Merged credit data in XML format																																					
MRG_RPTCOM	Merged credit report in TTY format																																					
MRG_RPTDTC	Merged credit Report in PDF format.																																					
MRG_DECISION	Decision results in XML format																																					
OFACRPT	Suspicious persons report in TTY format																																					
OFACXML	Suspicious persons report in XML format																																					
CMRESPONSE/DATASETS/DATA	STATUSCODE	<p>0 = Complete 1 = Incomplete</p>																																				
CMRESPONSE/DATASETS/DATA		Base64 Encoded Product Response.																																				

MRG_XML/MRG_XMLSTACK Credit Data

The MRG_XML and MRG_XMLSTACK products are XML data sets and are found in the CDATA section of the CMResponse.XML structure when the MRG_XML or MRG_XMLSTACK products are ordered.

The MRG_XML and MRG_XMLSTACK data sets are organized as 15 Segments:

IDENTIFICATION
 ADDRESS
 EMPLOYMENT
 INQUIRY
 CONSUMER_STATEMENT
 CREDITOR
 AKA
 CONSUMER_REFERRAL
 BANKING
 SCORE
 MISCELLANEOUS
 PUBLIC_RECORD
 BUREAU_ERROR
 TRADELINE

Merged Bureau Distinction

These segments represent a merged view of credit data from any number of repositories. Based upon a SOURCE field, the segment can be identified as representing a combination of Equifax, Experian or TransUnion.

Similarly, not all of the bureaus may consider an item as derogatory. As such credit measuring segments such as TRADELINE and PUBLIC_RECORD contain a DEROGIND field which indicates which bureaus consider the data derogatory.

SOURCE and DEROGIND EXAMPLE:

1	Equifax
2	Experian
3	Equifax, Experian
4	TransUnion
5	Equifax, TransUnion
6	Experian, TransUnion
7	Equifax, Experian, TransUnion

MRG_XMLSTACK Stacked Merge Data

While the 15 top level segments adequately represent a merged data set, often it is desirable to also list a stacked merge data set. In this fashion, a

cross bureau merged picture can be shown as well as a picture of each of the bureaus.

With the exception of the BUREAU_ERROR Segment, all segments contain a sub node named INTRA. The INTRA node contains the same field nodes as its parent node; and represents the un-merged credit data from each of the bureaus. There will be up to three INTRA nodes within each segment. Each INTRA node represents one credit repository as indicated by a Bureau attribute.

EXAMPLE:

INTRA Bureau="EFX"	Identifying this sub-segment as originating from Equifax.
INTRA Bureau="EXP"	Identifying this sub-segment as originating from Experian.
INTRA Bureau="TUC"	Identifying this sub-segment as originating from TransUnion

A schema for the XML_MERGE product can be found at <https://webservice.credimetrics.com/schemas/mergeresponse.xsd>, as well as a sample xml file at <https://webservice.credimetrics.com/schemas/mergeresponse.xml>.

USING THE CLIENT OBJECT

Customer systems operating in the Microsoft environment can take advantage of the Credmetrics Merge Client Object. This object accepts parameters from the customer's system, creates the appropriate XML document and interacts with the Credmetrics SOAP listener at the Credmetrics host.

Customers using this object will typically be web-based ASP (Active Server Page) applications, enterprise developed applications using Visual Basic or any other Microsoft Windows application that can interface with an ActiveX DLL.

NOTE: THE CLIENT OBJECT CURRENTLY DOES NOT SUPPORT THE PRBC FICO XML PRODUCT.

CMMERGE CLIENT METHODS

The CMMergeClient Object's REQUEST class provides the following methods:

CreateXMLRequestString()

Creates an XML document from the current settings. Useful for applications that wish to perform their own SOAP dialogue with ; and simply need a way to create the XML document

GetResponse(*ByVal ProductCode As String, ByVal StatusCode As String, ByVal StatusMessage As String*) As String

Extracts the product data for the specified ProductCode from the returned XML document from . Additionally, any status code or message related to that particular product code is returned in the parameters.

PlaceOrder()

Sends the XML request document to the SOAP Listener and waits for the response.

SetRequestor(*ByVal LoginName As String, ByVal Password As String*)

Sets the customer login name and password for authentication with .

WriteResponseToDisk(*ByVal ProductCode, ByVal ReportPath As String, _ ByRef StatusCode As String, ByRef StatusMessage As String*) As

Integer

Similar to the GetResponse method, the WriteResponseToDisk method extracts the product data for the specified ProductCode from the returned XML document from and writes that data to a local disk file. Additionally, any status code or message related to that particular product code is returned in the parameters.

CMMERGE CLIENT PROPERTIES

TheCMMergeClient Object's REQUEST class provides the following properties:

CompletionDate – returns the date and time from that the order was completed.

OrderKey – The order key assigned by when the product is returned; or the order key assigned by Credmetrics to be referenced on a re-access.

OrderStatus – The status code of the current order.

OrderMessage – The English equivalent of the status code.

CMMERGE CLIENT CLASSES

The CMMergeClient Object provides the following classes:

CONSUMER - A class that contains information regarding the consumer on which the credit data is being ordered.

Properties:

ECO A Valid values are "I" for Individual or "J" for Joint access.

Methods:

SetSubject(*ByVal Surname As String, ByVal FirstName As String, _
ByVal MidName As String, ByVal Generation As String, _
ByVal SSN As String, ByVal Age As String*)

SetSubjectCRA(*ByVal CRASegment As String*)

Used to add a fully formatted CRA segment as defined by the FICO Expansion Score specifications. To conform with ' edit rules, however, the XML tags MUST be upper case.

SetSpouse(*ByVal Surname As String, ByVal FirstName As String, _
ByVal MidName As String, ByVal Generation As String, _
ByVal SSN As String, ByVal Age As String*)

Used to add a fully formatted CRA segment as defined by the FICO Expansion Score specifications. To conform with ' edit rules, however, the XML tags MUST be upper case.

SetSpouseCRA(*ByVal CRASegment As String*)

SetCurrentAddress(*ByVal Address As String, ByVal City As String, ByVal State As String, ByVal ZipCode As String*)

SetFormerAddress(*ByVal Address As String, ByVal City As String, ByVal State As String, ByVal ZipCode As String*)

DATASOURCES - A class containing repository subcodes, profiles and pass through product information

Properties:

UseEquifax as boolean. TRUE if requesting Equifax data

UseExperian as boolean. TRUE if requesting Experian data

UseTransUnion as boolean. TRUE if requesting TransUnion data

UsePRBC as Boolean. TRUE if requesting PRBC data

PRBCGetUpdated as Boolean. TRUE if requesting an updated PRBC file after an original PRBC file has been ordered for this OrderKey. NOTE: this only affects the behavior of a re-ordered product. Normally, re-ordered products use the same PRBC data as from a previous order. Setting this value to TRUE causes a new PRBC data file to be used for this re-ordered product.

Methods:

SetEquifax(*ByVal Preamble As String, ByVal SubCode As String, _
ByVal Password As String, ByVal Purpose As String, _
ByVal EndUser as string, ByVal Profile as String, _
Optional ByVal PassThruProduct as string, _
Optional ByVal RawData As String, _
Optional ByVal RawDataFile As String*)

SetEquifaxScoreModels(*ByVal ModelIds as string*)
Comma delimited string of score model ids.

SetEquifaxAddOns(*ByVal AddOns as string*)
Comma delimited string of add on features.

SetExperian(*ByVal Preamble As String, ByVal SubCode As String, _
ByVal Password As String, ByVal Purpose As String, _
ByVal EndUser as string, ByVal Profile as string, _
Optional ByVal PassThruProduct as String, _
Optional ByVal RawData As String, _
Optional ByVal RawDataFile As String*)

SetExperianScoreModels(*ByVal ModelIds as string*)
Comma delimited string of score model ids.

SetExperianAddOns(*ByVal AddOns as string*)
Comma delimited string of add on features.

SetTransUnion(*ByVal Market As String, ByVal SubMarket As String, ByVal
IndustryCode As String, ByVal SubCode As String, _
ByVal Password As String, ByVal Purpose As String, _
ByVal EndUser as string, ByVal Profile as string, _
Optional ByVal PassThruProduct as String, _
Optional ByVal RawData As String, _
Optional ByVal RawDataFile As String*)

SetTransUnionScoreModels(*ByVal ModelIds as string*)
Comma delimited string of score model ids.

SetTransUnionAddOns(*ByVal AddOns as string*)

Comma delimited string of add on features.

SetPRBC(*ByVal SubCode As String, _
ByVal Password As String, ByVal Purpose As String, _
ByVal EndUser as string, ByVal Profile as string, _
Optional ByVal RawData As String, _
Optional ByVal RawDataFile As String*)

DECISIONS - A class containing the name of the decision profile to be run and any optional decision parameters required by the profile.

Properties:

ProfileName as string. The name of the decision profile being executed.

ResultsNameList as string array. An array of names of results parameters returned by the decision.

XML as string. The XML product data returned by the REQUEST class is passed to the DECISION class via this property for processing.

PRBCGetUpdated as Boolean. True forces to obtain a fresh copy of a PRBC data file even though one already has been accessed from PRBC.

Methods:

AddParameters(*ByVal ParmName As String, ByVal ParmValue As String*)

Adds a decision request parameter by name and value to an internal collection of parameters used by the decision.

GetResultsByName(*ByVal ParmName As String*)

Retrieves the value for a given decision result parameter name.

PRODUCTS - A class containing product codes to be ordered in this request.

Properties:

ProductsList as Collection. A Visual Basic Collection containing the list of all the products being returned.

Methods:

AddProduct(*ByVal ProductCode As String, Optional ByVal Options as string*)

Adds a product code to the request XML document.

RemoveProduct(*ByVal ProductCode As String*)

Removes a product code from the request XML document.

RemoveAllProducts()

Removes all product codes from the request XML document.

REQUEST - The main class of the CMMergeClient containing references to other classes and basic properties and methods. (See the CMMERGE CLIENT METHODS for details.)

CLIENT OBJECT SAMPLES

The code herein represents a sample of various ordering scenarios.

ORDERING MERGED PRODUCTS

This example orders all of the merged products in a single order.

```

Dim oCMMergeClient As New CMergeClient.Request
Dim i As Integer
Dim MyStatusCode as string
Dim MyStatusMessage as string
' *****
' * SET THE LOGIN INFO
' *****
oCMMergeClient.SetRequestor txtLoginName, txtPassword
' *****
' * SET THE CONSUMER INFO
' *****
oCMMergeClient.Consumer.ECOA = "I"
oCMMergeClient.Consumer.SetCurrentAddress "111 AVERY RD", "ROME", "GA", "30361"
oCMMergeClient.Consumer.SetSubject "CRAWFORD", "ROBERT", "M", "JR", "143777890", "28"
' *****
' * SET THE BUREAU DATA SOURCE INFO
' *****
' USE MY OWN PRIVATE EQUIFAX SUBCODE AND PASSWORD INFO
oCMMergeClient.Datasources.SetEquifax MyPreamble, MySubCode, MyPassword, "", "", ""
oCMMergeClient.Datasources.UseEquifax = True

' REFERENCE THE EXPERIAN PROFILE ON FILE AT CREDMETRICS
oCMMergeClient.Datasources.SetExperian "", "", "", "", "", "MYEXPPROFILE"
oCMMergeClient.Datasources.UseExperian = True

'DON'T USE ANY TRANS UNION DATA IN THIS REQUEST
oCMMergeClient.Datasources.UseTransUnion = False

' ADD PRBC DATA TO THIS REQUEST
oCMMergeClient.DataSources.SetPRBC "", "", "", "", "MYPRBCPROFILE"
oCMMergeClient.DataSources.UsePRBC = True

' *****
' * SET THE PRODUCT REQUEST INFO
' *****
oCMMergeClient.Products.AddProduct "MRG_XML"
oCMMergeClient.Products.AddProduct "MRG_RPTCOM"
oCMMergeClient.Products.AddProduct "MRG_RPTDTC"
oCMMergeClient.Products.AddProduct "MRG_DECISION"
oCMMergeClient.Products.AddProduct "OFACXML"
' *****
' * SINCE DECISION WAS REQUESTED, SET THE ADDITIONAL DECISION INFO REQUIRED
' * BY THE 'MYDECISIONPROFILE' SCRIPT ON FILE AT CREDMETRICS
' *****
oCMMergeClient.Decisions.AddParameters "INCOME", "50000"
oCMMergeClient.Decisions.AddParameters "LOANAMOUNT", "39544"
oCMMergeClient.Decisions.ProfileName = "MYDECISIONPROFILE"

Me.lstErrors.Clear
oCMMergeClient.PlaceOrder

txtCompletionDate = oCMMergeClient.CompletedDate
txtOrderKey = oCMMergeClient.OrderKey
txtOrderMessage = oCMMergeClient.OrderMessage
txtOrderStatus = oCMMergeClient.OrderStatus
If oCMMergeClient.OrderStatus = "0" Then
    MyTextBox = oCMMergeClient.GetResponse ("MRG_RPTCOM", MyStatusCode, MyStatusMessage)
    oCMMergeClient.WriteResponseToDisk "OFACXML", "C:\ofacxml.xml", "", ""
    oCMMergeClient.WriteResponseToDisk "MRG_RPTCOM", "C:\mrg_rptcom.txt", "", ""
    oCMMergeClient.WriteResponseToDisk "MRG_RPTDTC", "C:\mrg_rptdctc.pdf", "", ""

```

```

oCMMergeClient.Decisions.XML = oCMMergeClient.GetResponse("MRG_DECISION", "", "")
MyForm.txtPassFail = oCMMergeClient.Decisions.GetResultsByName("PASSFAIL")
MyForm.txtReason = oCMMergeClient.Decisions.GetResultsByName("REASON")
Else
  For i = 1 To oCMMergeClient.Errors.Count
    MyForm.lstErrors.AddItem oCMMergeClient.Errors(i)("CODE") & "-" &
oCMMergeClient.Errors(i)("MESSAGE")
  Next i
End If

```

ORDERING PASS THROUGH PRODUCTS

This example orders an Equifax DTEC TTY report from Equifax.

```

Dim oCMMergeClient As New oCMMergeClient.Request
Dim i As Integer
'*****
' * SET THE LOGIN INFO
'*****
oCMMergeClient.SetRequestor MyForm.txtLoginName, MyForm.txtPassword
'*****
' * SET THE CONSUMER INFO
'*****
oCMMergeClient.Consumer.SetSubject "", "", "", "", "143777890", ""
'*****
' * SET THE BUREAU DATA SOURCE INFO
'*****
oCMMergeClient.Datasources.SetEquifax txtPreamble, txtSubCode, txtPassword, _
  "", "", "", " EFXDTECTTY"
oCMMergeClient.Datasources.UseEquifax = True
oCMMergeClient.Datasources.UseExperian = false
oCMMergeClient.Datasources.UseTransUnion = False
'*****
' * SET THE PRODUCT REQUEST INFO
'*****
oCMMergeClient.Products.AddProduct " EFXPASSTHRU"

Me.lstErrors.Clear
oCMMergeClient.PlaceOrder

MyForm.txtCompletionDate = oCMMergeClient.CompletedDate
MyForm.txtOrderKey = oCMMergeClient.OrderKey
MyForm.txtOrderMessage = oCMMergeClient.OrderMessage
MyForm.txtOrderStatus = oCMMergeClient.OrderStatus
If oCMMergeClient.OrderStatus = "0" Then
  oCMMergeClient.WriteResponseToDisk " EFXPASSTHRU ", "C:\efxdtecreport.txt", "", ""
Else
  For i = 1 To oCMMergeClient.Errors.Count
    MyForm.lstErrors.AddItem oCMMergeClient.Errors(i)("CODE") & "-" &
oCMMergeClient.Errors(i)("MESSAGE")
  Next i
End If

```

ORDERING PRBC XML AND FICO EXPANSION SCORE

This example orders a PRBC XML file and a FICO Expansion Score.

Note: The FICO Expansion score expects a CRA segments formatted to their specifications to be attached to each borrower (Subject and/or Spouse).

```

Dim oCMMergeClient As New CMMergeClient.Request
Dim i As Integer
' *****
' * SET THE LOGIN INFO
' *****
oCMMergeClient.SetRequestor MyForm.txtLoginName, MyForm.txtPassword
' *****
' * SET THE CONSUMER INFO (SUBJECT)
' *****
oCMMergeClient.Consumer.SetSubject MyForm.txtSubLastName, _
    MyForm.txtSubFirstName, MyForm.txtSubMidName, _
    MyForm.txtSubSSN, MyForm.txtSubDOB

oCMMergeClient.Consumer.SetSubjectCRA myFormattedSubjectCRASegment

' *****
' * SET THE CONSUMER INFO (SPOUSE)
' *****
oCMMergeClient.Consumer.SetSpouse MyForm.txtSpoLastName, _
    MyForm.txtSpoFirstName, MyForm.txtSpoMidName, _
    MyForm.txtSpoSSN, MyForm.txtSpoDOB

oCMMergeClient.Consumer.SetSubjectCRA myFormattedSpouseCRASegment

' *****
' * SET THE BUREAU DATA SOURCE INFO
' *****
oCMMergeClient.Datasources.SetPRBC MyForm.txtPRBCSubcode, _
    MyForm.txtPRBCSubCode, MyForm.txtPRBCPassword, _
    MyForm.txtPRBCPurpose, MyForm.txtPRBCEndUser, _
    MyForm.txtPRBCProfile
oCMMergeClient.Datasources.UsePRBC = True
' *****
' * SET THE PRODUCT REQUEST INFO
' * NOTE: PRBC_XML MUST PRECEDE PRBC_FICO_XML
' *****
oCMMergeClient.Products.AddProduct "PRBC_XML"
oCMMergeClient.Products.AddProduct "PRBC_FICO_XML"

Me.lstErrors.Clear
oCMMergeClient.PlaceOrder

MyForm.txtCompletionDate = oCMMergeClient.CompletedDate
MyForm.txtOrderKey = oCMMergeClient.OrderKey
MyForm.txtOrderMessage = oCMMergeClient.OrderMessage
MyForm.txtOrderStatus = oCMMergeClient.OrderStatus
If oCMMergeClient.OrderStatus = "0" Then
    oCMMergeClient.WriteResponseToDisk " PRBC_XML ", "C:\prbc.xml", "", ""
    oCMMergeClient.WriteResponseToDisk " PRBC_FICO_XML ", "C:\prbc_fico.xml", "", ""
Else
    For i = 1 To oCMMergeClient.Errors.Count
        MyForm.lstErrors.AddItem oCMMergeClient.Errors(i)("CODE") & "-" &
oCMMergeClient.Errors(i)("MESSAGE")
    Next i
End If

```